

HB-800

31.5" HORIZONTAL BAND RESAW

Features

- 800mm (32") diameter cast iron wheels without rubber on rims.
- Ground finish cast iron work table – tilts to 45°.
- Heavy gauge fabricated steel body to minimize vibration.
- Top and bottom precision saw guides to accept up to 100mm (4") wide saw blades.
- Rack and pinion rise and fall of top saw guides.
- Top wheel up and down adjustment by handwheel.
- Brush oil drip unit to clean bottom wheel rim.
- Heavy adjustable rip fence to left of blade with idle rollers for friction free feeding.
- Equipped with Model HF-150A serrated vertical-roller power feed unit for continuous feeding of timber.
- One saw blade provided – 5500mm x 100mm x 19 gauge swaged tooth resaw blade.
- Foot brake on bottom wheel for emergency stops.
- Dust extraction outlet on side of machine 100mm diameter.
- Transparent perspex eye protection guard over top guides.
- Adjustable pneumatic side pressure of feed roller against timber.
- Centralised electrical control panel with all switches grouped together.



Technical Data:

Size of work table	800 mm x 1150 mm
Cutting capacity (height x width)	390 mm x 778 mm
Width of wheel rims	90 mm
Blade length	Max. 5515 mm Min. 5485 mm
Nett weight of machine with feeder	775 kgs
Height of feed roller hob	150 mm
Diameter of feed roller hob	200 mm
Feed speed variable	from 5 – 20 metres/min
HF-150A feed unit motor	1 hp
Maximum width from saw blade to feed hob	125 mm
Standard width from saw blade to roller fence	120 mm
(Extra pair of tapped holes can be provided in Work table to increase width to approx 220mm)	
Main Motor	10hp 3 phase

WELDLINE

WOODWORKING MACHINERY

A Division of Costa Group of Companies Pty Ltd

www.weldline.com.au

Telephone Number: (08) 8280 6440 Facsimile Number: (08) 8280 9110

Lot 11 Angle Vale Crescent, Burton. S.A. 5110