

# HB-900HA

## 36" HORIZONTAL BAND RESAW

### Features

- 900mm (36") diameter cast iron wheels without rubber on rims.
- Large ground finish cast iron work table.
- Heavy gauge fabricated steel body to minimize vibration.
- Top and bottom precision saw guides to accept up to 125mm (5") wide saw blades.
- Rack and pinion rise and fall of top saw guides.
- Top wheel up and down adjustment by handwheel.
- Brush oil drip unit to clean bottom wheel rim.
- Heavy adjustable rip fence to left of blade with idle rollers for friction free feeding.
- Integral heavy serrated vertical-roller power feed hob for continuous feeding of timber.
- One saw blade provided – 5995mm x 125mm x 19 gauge swaged tooth resaw blade.
- Foot brake on bottom wheel for emergency stops.
- Two dust extraction outlets on machine each of 100mm diameter.
- Adjustable pneumatic side pressure of feed roller against timber.
- Automatic switch protruding from work table. When depressed by incoming timber, it brings feed roller in, to make contact with timber, to feed it through to be cut.
- Centralised electrical control panel with all switches grouped together.



### **Technical Data:**

Size of work table	1400 mm x 850 mm
Cutting capacity (height x width)	400 mm x 720 mm
Width of wheel rims	100 mm
Blade length	5995 mm
Nett weight of machine	1750 kgs
Height of feed roller	160 mm
Diameter of feed roller	260 mm
Feed speed variable	from 8 – 32 metres/min
Maximum width from saw blade to feed hob	350 mm
Guide fence dimensions	800 mm x 230 mm
Maximum width from saw blade to roller fence	370 mm
Main saw motor	30 hp 3 phase
Feed motor	2 hp 3 phase



A Division of Costa Group of Companies Pty Ltd

[www.weldline.com.au](http://www.weldline.com.au)

Telephone Number: (08) 8280 6440 Facsimile Number: (08) 8280 9110

Lot 11 Angle Vale Crescent, Burton. S.A. 5110