

# YFC-18

## PNEUMATICALLY OPERATED UNDER TABLE DOCKING SAW



### Features

- Available in either right or left hand configuration to suit work flow.
- 455mm (18") diameter saw blade, travelling up vertically to cut timber, from rest position below work table.
- Cast iron work table on fabricated steel base.
- Heavy moving safety guard to strongly clamp the timber to be cut by pneumatic pressure.
- Overhead safety guards 300mm on each side of saw blade.
- Two push button switches on front of machine to commence operation.
- Hinged door on front of machine for easy access to working parts.
- TCT saw blade included, with 120 teeth.
- A well finished, fast and reliable docking saw.

### Optional

Infeed and outfeed roller tables 3000mm long, each side of machine.

Plain roller table on infeed and aluminium fence, three length stops and metric scale on outfeed table.

10 Rollers on each table.

### **Technical Data:**

Maximum section of workpiece	245mm wide x 108mm high
(SMALLER WIDTH = GREATER HEIGHT)	327mm wide x 28mm high
Saw blade motor	10hp, three phase
Compressed air consumption	11.5 cfm @ 90 psi (for 45 cycles/minute)
Dust extraction outlet on rear	100mm diam (4")

# WELDLINE

## WOODWORKING MACHINERY

A Division of Costa Group of Companies Pty Ltd

[www.weldline.com.au](http://www.weldline.com.au)

Telephone Number: (08) 8280 6440 Facsimile Number: (08) 8280 9110

Lot 11 Angle Vale Crescent, Burton. S.A. 5110