

# HA-120

## BENCH EDGE BANDER MACHINE

for pre-glued edgestrip up to 2mm thick



### Features

- 1500 watt heater/blower unit to re-activate glue.
- Variable heat control switch with cooling-off settings.
- Pneumatic cut-off guillotine for roll-edgestrip (melamine, PVC or veneer)
  - Controlled by 2 limit switches in work table.
- Single phase 240 volt electrics throughout.
- Sheet steel machine body with anti-friction strips on work table.
- Driven polyurethane pressure roller after edgestrip application position.
- Complete with foot pedal control of cut-off guillotine – used when shaped work-piece will not activate table limit switches.
- Shaped panels can be edged by removing outfeed fence.
- Sheet steel tray to support rolls of edgestrip.
- Note: No flush end trimming or top and bottom trimming.

### Technical Data

Thickness of panels	10 to 33 mm
Thickness range of edgestrips	0.4 to 2 mm
Speed of driven pressure roller	4.3 metres / min
Heat up time of heater / blower unit	3 – 5 minutes
Compressed air supply required	100 psi
Machine dimensions	730 x 555 x 350 mm
Machine weight (approx)	42 kgs



A Division of Costa Group of Companies Pty Ltd

[www.weldline.com.au](http://www.weldline.com.au)

Telephone Number: (08) 8280 6440 Facsimile Number: (08) 8280 9110

Lot 11 Angle Vale Crescent, Burton. S.A. 5110