

AF-16 CO-MATIC BANDSAW FEED UNIT

with vertical Feed Roller, for use on a bandsaw or band resaw



Features

- Large serrated steel or polyurethane covered feed rollers on spring loaded arm mounted on right side of blade.
- Top roller can be adjusted up and down to suit wood.
- Arm supporting feed roller on one end and motor on the other, mounted on centre support bolted to bandsaw table.
- Six different feed speeds from two-speed motor and belt change with 3 pulley combinations.
- Guide fence mounted on left side of blade, can be set to cut required widths of timber.
- CO-MATIC – undisputed world leading supplier of power feeders!

Technical Data

Range of 6 feeds speeds	from 1.5 to 11.4 metres/min
Dimensions of two feed rollers	120 mm diam x 25 mm height
Table to top of top roller	120 mm max
Dimensions of guide fence	400mm long x 175mm height
Three phase drive motor	0.25 hp
Maximum clearance roller to blade	100 mm
Nett weight of feeder	28 kgs

WELDLINE

WOODWORKING MACHINERY

A Division of Costa Group of Companies Pty Ltd

www.weldline.com.au

Telephone Number: (08) 8280 6440 Facsimile Number: (08) 8280 9110

Lot 11 Angle Vale Crescent, Burton. S.A. 5110