

# **AF-C3** CO-MATIC CURVED WORK POWER FEED UNIT

## **Features**

- Three feed rollers with abrasion resistant vulcanised rubber 'tyres'.
- One end roller manually adjustable upwards or downwards in relation to other two rollers, then locked with kipp lever.
- Roller moved upwards to feed concave workpieces.
- Roller moved downwards to feed convex workpieces.
- Curved workpieces to be minimum 300mm radius.
- Four different feed speeds for various operations – forward and reverse.
- Universally adjustable mounting stand to allow feeding operations vertically, horizontally or at any angle in between.
- Turning type electrical switch for 2-speed motor and reversible gears to select required speeds.
- A versatile feed unit that can be used on many different types of woodworking machines when curved work is done.
- CO-MATIC – undisputed world leading supplier of power feeders!



## **Technical Data**

Three phase electric motor	Two speed 1hp
Vertical adjustment stroke	245 mm
Diameter of feed rollers	120 mm
Width of feed rollers	60mm (can be doubled to 120mm if required)
Total nett weight	65 kgs
Four available feed speeds	4, 8, 11 and 22 m/min
Vertical roller suspension limit	20 mm



A Division of Costa Group of Companies Pty Ltd

[www.weldline.com.au](http://www.weldline.com.au)

**Telephone Number: (08) 8280 6440 Facsimile Number: (08) 8280 9110**

**Lot 11 Angle Vale Crescent, Burton. S.A. 5110**