

# JRS-12TK

## JO-WAY STRAIGHT LINE RIP SAW



### Features

- Standard Model - 85mm maximum cut depth
- Power driven feed of timber by heavy duty precision bottom feed chain set into work table.
- Feed chain ensures timber is cut perfectly straight, even if incoming stock is curved on both sides.
- Multiple anti-kickback devices ensure safe feeding of timber.
- Side guard and rear guard ensure safe operation.
- Handwheel rise and fall of cutting height adjustment.
- Handwheel adjustment of infeed fence positioning.
- Elevated, convenient electrical control panel.
- Automatic oil pump lubrication of feed chain for long life.

### Technical Data

Maximum saw blade diameter	305 mm
Maximum workpiece thickness	85 mm
Throat capacity of machine	460 mm
Feed speed range (4 speeds)	15, 20, 25 & 30 metres / min
Dust extraction outlet diameter	125 mm
Saw spindle motor	15 hp
Feed drive motor	3 hp
Nett weight of machine	900 kgs

# WELDLINE

## WOODWORKING MACHINERY

A Division of Costa Group of Companies Pty Ltd

[www.weldline.com.au](http://www.weldline.com.au)

Telephone Number: (08) 8280 6440 Facsimile Number: (08) 8280 9110

Lot 11 Angle Vale Crescent, Burton. S.A. 5110