

TC-12

PROFESSIONAL TABLE SAW

Illustration shows machine with optional Sliding Table

Features

- Heavy cast iron interior housing supporting sealed saw arbor bearings.
- Heavy sheet steel machine body with ground cast iron table.
- Handwheel blade rise and fall to adjust cutting thickness.
- Handwheel blade tilting from vertical to 45° angle.
- Mitre gauge sliding in table slots either side of blade.
- Excellent rip fence, with positive locking, square every time.
- Magnifying glass to easily read measuring tape for accuracy.
- Magnetic electrical switch gear with protruding stop button, overload protection and no-volt release.
- Overhead SUVA type safety guard on tube-steel frame included, to comply with relevant safety standards.
- Riving knife behind blade rises and falls and tilts with the blade to comply with relevant safety standards.
- An accurate, reliable table saw with a proven record of performance all over Australia.



OPTIONAL EXTRA

Precision sliding crosscutting table assembly with 1250mm cutting stroke and aluminium measuring fence.

Technical Data

Maximum diameter of saw blade	305 mm (12")
Maximum depth of cut @ 90°	102 mm
Maximum depth of cut @ 45°	70 mm
Diameter of saw blade arbor	30 mm
Size of cast iron work table	1220 x 762 mm
Height of work table from floor	857 mm
Maximum ripping capacity to right of blade	1270 mm
Motor Single Phase	3hp or Three Phase 5hp
Nett weight of machine	260 kg



A Division of Costa Group of Companies Pty Ltd

www.weldline.com.au

Telephone Number: (08) 8280 6440 Facsimile Number: (08) 8280 9110

Lot 11 Angle Vale Crescent, Burton. S.A. 5110