

SR-680

RU LONG HIGH SPEED OVERHEAD ROUTER

Features

- 680mm Throat distance from column to cutter spindle.
- Heavy steel and cast iron construction of machine.
- Large one-piece work table, 900mm wide x 600mm deep.
- Work table tilting to maximum 45 degrees.
- Retractable guide pin in centre of work table, plus a guide fence of full 900mm width of table.
- Pneumatic up and down movement of work head activated by foot pedal.
- Six pre-set height stops provided on head movement.
- Work table adjustable for height by convenient handwheel.
- No. 2 morse taper in cutter spindle to accept collet chuck.
- Three collets provided – 1/2", 3/8" and 1/4".
- Safety guard incorporating dust extraction outlet, with brush around rim to improve extraction efficiency.
- Fully enclosed sheet steel machine body.



Technical Data

| | |
|---------------------------------------|---------------------|
| Two cutter spindle speeds | 10,000 & 20,000 rpm |
| Stroke of pneumatic head movement | 90 mm |
| Stroke of vertical table adjustment | 200 mm |
| Size of large work table | 600 mm x 900 mm |
| Three guide pins of diameters | 1/4", 3/8" and 1/2" |
| Three phase, two speed electric motor | 5 hp |

WELDLINE

WOODWORKING MACHINERY

A Division of Costa Group of Companies Pty Ltd

www.weldline.com.au

Telephone Number: (08) 8280 6440 Facsimile Number: (08) 8280 9110

Lot 11 Angle Vale Crescent, Burton. S.A. 5110